

600

NEW



30 L/min

Brass Seat - *Sede tenuta ottone*: Ø 12 mm

Max pressure - *Pressione max*: 6 bar

Max width - *Ingombro max*: 245 mm



The new 600 series (PEKI® 8G) fulfils the requirement of users who need both a high flow of water and a small size. The peculiarity is the ø12mm seat bore, usually available on 3/4" to 1" valves. The length of the lever and the new shape of the float ball, such as the 650-R in the picture, ensures that by connecting with the pressure lines the float valve close safely.

The basic version 600-1/2" is supplied with 650-R oval float ball.

La nuova serie 600 (PEKI® 8G) soddisfa le esigenze degli utenti che richiedono sia un elevato flusso di acqua, sia un ingombro ridotto. La particolarità è il foro della sede di tenuta ø12mm, solitamente disponibile su valvole da 3/4" a 1". La lunghezza dell'asta e la nuova forma della sfera, come la 650-R nella foto, assicura che i rubinetti a galleggiante chiudano in modo sicuro anche in presenza di collegamenti diretti con le linee idriche.

La versione base 600-1/2" viene fornita completa di sfera ovale 650-R.

Art. code	Connection DN	Pressure min	Pressure max	KVS L/min @ 3 bar	Float/Sfera
600-1/2"	1/2"G	0 bar	6 bar	30	130/68/90 mm
650-R					130/68/90 mm



Commercial info veit@esseti-srl.com

Orders-Shippings ufficio@esseti-srl.com
www.esseti-srl.com



ST SRL

Via Fermi 64 - 25030 Brandico (Bs) Italy